

LED Square Wall Sconce



Project:

Location:

Catalog #:

Quantity:

Features

Teslyte ET6161 Series is a contemporary and stylish square wall sconce that features both uplight, downlight or both up and downlight. The ET6161 wall sconce is designed to provide exceptional illumination and performance and its modern shape blends into the surroundings making it the ideal choice for illuminate and enhance building exteriors and interiors.

- **Housing:**
 - Extruded aluminum housing
 - Die casting aluminum cover ring and base.
 - Stainless steel screws and plate.
 - Imported silicon rubber ring.
- **Finish:**
 - Powder coat finish that provides superior resistance to corrosion and weathering.
- **Lens:**
 - High intensity tempered glass.
- **Optics:**
 - High power led 3-step MacAdam Ellipse
 - Optics are engineered for superior field-to-beam ratio.
- **LEDs:**
 - Integral highly efficient LED module and driver.
 - Input Voltage: 100-277 V_{AC} (50/60 Hz)
- **Applications:**
 - Suitable for outdoor and indoor for Residential or Commercial
- **Mounting:** wall mount
- **Ratings:**
 - Suitable for wet locations. IP 65.
 - 5-year warranty

Ordering Information

Product code	Power	CCT (K)	Beam Angle	Ra	Finish	Optional
<input type="text"/>	- <input type="text"/>	- <input type="text"/>	- <input type="text"/>	- <input type="text"/>	- <input type="text"/>	- <input type="text"/>
ET6161	C40 - 20W x2	3 - 3000K 4 - 4000K 6 - 6000K	15 - 15° 23 - 23° 38 - 38° 45 - 45° 60 - 60°	80 - Ra80 90 - Ra90	B - Black W - White G - Gray Z - Mineral S - Silver	T - 20° Tilt M - Marine ambient corrosion resistance DMG - 0-10V Dimming
ET6161D - Downlight	C20 - 20W					
ET6161U - Uplight						

Note: Fixtures must be grounded in accordance with national, state, and/or local electrical codes. Failure to do so may result in serious personal injury

Mechanical Dimensions

