

LED Decorative Post Top



Project:

Location:

Catalog #:

Quantity:

Features

Teslyte EW-S101MB3F Series is a sleek three-arm support styling, aesthetic architectural design integrated with an advanced LED optical system to deliver an excellent combination of performance and visual comfort. This EW-S101MB3F series brings decorative style to area and site lighting.

- **Housing:**
 - Aluminum alloy die-casting for superior durability
 - Silicone gaskets enable an IP66 rated optical compartment
 - Stainless steel hardware with properly secure all components within the housing
- **Lens:**
 - Optical PMMA LGP plus high-degree diffusion outdoor PC lens providing a high degree of visual comfort
- **LEDs:**
 - Highly efficient LEDs and quality driver providing luminaire output efficacy up to 125 LPW
- **Applications:** Streetscapes, parks, green spaces, campuses, and gathering areas
- **Mounting:**
 - 3" or 4" Post top mount for 2-3/8" OD Tenon
 - Flush mount 2-3/8" OD pole
 - Secure with 6 sets of concealed stainless steel screws
- **Ratings:** ETL, IP66 rated, suitable for wet locations
- **Warranty:** 5 years

Ordering Information

Product code	Dimming option	Wattage	CCT(K)	Finish
EW-S101MB3F	-	-	-	-
	A - No Dimming	025 - 25W	22 - 2200K	DB - Dark Bronze
	B - 1-10V Dimming	035 - 35W	27 - 2700K	LG - Light Gray
	C - Timer Dimming with 3 Timer Modes	060 - 60W	40 - 4000K	BL - Black
	D - DALI Controllable with Class II DALI-2 Driver Integrated with Always-on Auxiliary Power, Ready for Sensor Controllable (220 – 240 Vac input Only)		50 - 5000K	
	E - DALI Controllable with Class I DALI-2 Driver Integrated with Always-on Auxiliary Power, Ready for Sensor Controllable		60 - 6000K	

Note: Fixtures must be grounded in accordance with national, state, and/or local electrical codes. Failure to do so may result in serious personal injury

Mechanical Dimensions

