



## Hexlyte™ Tree Ring LED

Project:

Location:

Catalog #:

Quantity:



### Features

Hexlyte™ is a revolutionary idea in illuminating upper tree growth for decorative purposes, while providing the ability for downlight for security and pathway illumination. Hexlyte™ integrates the illumination source into a single piece, high strength, extruded aluminum housing. The very wide distribution of this illumination source, using the latest LED technology, allows for the physical size to be much smaller than traditional tree rings.

- **Construction:**
  - Heavy duty extruded aluminum housing
  - Wet location listed
- **Lens:**
  - Self-cleaning, abrasion resistance acrylic lenses, extreme temperature performance
- **Voltage and LEDs:**
  - 24VDC
  - Latest linear COB LEDs minimizing the “dot effect”
  - Driver: Remoted driver 120V-277V
  - Warranty: 3 years
  - Phone App. Driver available (consult factory)
  - Front Shields available (consult factory)



**Ordering Information**
**Fit trunk size 7"-11" Diameter**

Product Code	Total Wattage	# Segments Up/Down	CCT (K)	Finish	Options
<b>HL-10R</b>	- [ ]	- [ ]	- [ ]	- [ ]	- [ ]
Lumens: 815lms per segment	<b>25- 25W</b> <b>50- 50W</b> (System wattage)	<b>30- 3 up/0 down 25W</b> <b>03- 0 up/3 down 25W</b> <b>33- 3 up/3 down 25W</b> <b>Up/Down operate dependently</b> <b>66- 6 up/6 down 50W</b>	<b>30- 3000K</b> <b>40- 4000K</b> <b>MC- RGBW</b> (contact manufacturer for details)	Standard color <b>B- Black</b> <b>G- Gray</b> <b>Z- Bronze</b> Custom color (contact manufacturer)	<b>N- Non dimming</b> <b>D- 0-10V Dimming</b> <b>M- Marine grade</b>

**Fit trunk size 12"-17" Diameter**

Product Code	Total Wattage	# Segments Up/Down	CCT (K)	Finish	Options
<b>HL-13R</b>	- [ ]	- [ ]	- [ ]	- [ ]	- [ ]
Lumens: 1050lms per segment	<b>30- 30W</b> <b>60- 60W</b> (System wattage)	<b>30- 3 up/0 down 30W</b> <b>03- 0 up/3 down 30W</b> <b>33- 3 up/3 down 30W</b> <b>Up/Down operate dependently</b> <b>66- 6 up/6 down 60W</b>	<b>30- 3000K</b> <b>40- 4000K</b> <b>MC- RGBW</b> (contact manufacturer for details)	Standard color <b>B- Black</b> <b>G- Gray</b> <b>Z- Bronze</b> Custom color (contact manufacturer)	<b>N- Non dimming</b> <b>D- 0-10V Dimming</b> <b>M- Marine grade</b>

**Fit trunk size 18"-23" Diameter**




Product Code	Total Wattage	# Segments Up/Down	CCT (K)	Finish	Options
<b>HL-16R</b>	- [ ]	- [ ]	- [ ]	- [ ]	- [ ]
Lumens: 1400lms per segment	<b>40- 40W</b> <b>80- 80W</b> (System wattage)	<b>30- 3 up/0 down 40W</b> <b>03- 0 up/3 down 40W</b> <b>33- 3 up/3 down 40W</b> <b>Up/Down operate dependently</b> <b>66- 6 up/6 down 80W</b>	<b>30- 3000K</b> <b>40- 4000K</b> <b>MC- RGBW</b> (contact manufacturer for details)	Standard color <b>B- Black</b> <b>G- Gray</b> <b>Z- Bronze</b> Custom color (contact manufacturer)	<b>N- Non dimming</b> <b>D- 0-10V Dimming</b> <b>M- Marine grade</b>

**Fit trunk size 24"-27" Diameter**

Product Code	Total Wattage	# Segments Up/Down	CCT (K)	Finish	Options
<b>HL-19R</b>	- [ ]	- [ ]	- [ ]	- [ ]	- [ ]
Lumens: 1750lms per segment	<b>60- 60W</b> <b>120- 120W</b> (System wattage)	<b>Single operation 1 driver</b> <b>30- 3 up/0 down 60W</b> <b>03- 0 up/3 down 60W</b> <b>33- 3 up/3 down 60W</b> <b>Up/Down operate dependently</b> <b>66- 6 up/6 down 120W</b>	<b>30- 3000K</b> <b>40- 4000K</b> <b>MC- RGBW</b> (contact manufacturer for details)	Standard color <b>B- Black</b> <b>G- Gray</b> <b>Z- Bronze</b> Custom color (contact manufacturer)	<b>N- Non dimming</b> <b>D- 0-10V Dimming</b> <b>M- Marine grade</b>

Note: Fixtures must be grounded in accordance with national, state, and/or local electrical codes. Failure to do so may result in serious personal injury

**Mechanical Dimensions**

**10R- fit trunk size 7"-11"**

**13R- fit trunk size 12"-17"**

**16R- fit trunk size 18"-23"**

**19R- fit trunk size 24"-27"**
