

LED Decorative Post Top



Features

Teslyte PT-ED Series is a sleek three-arm support styling, aesthetic architectural design integrated with an advanced LED optical system to deliver an excellent combination of performance and visual comfort. This PT-ED series brings decorative style to area and site lighting.

- **Housing:**
 - Aluminum alloy die-casting for superior durability
 - Silicone gaskets enable an IP66 rated optical compartment
 - Stainless steel hardware with properly secure all components within the housing
- **Lens:** Optical PMMA LGP plus high-degree diffusion outdoor PC lens providing a high degree of visual comfort
- **LEDs:** Highly efficient LEDs and quality driver providing luminaire output efficacy up to 125 LPW
- **Applications:** Streetscapes, parks, green spaces, campuses, and gathering areas
- **Mounting:**
 - 3" or 4" Post top mount for 2-3/8" OD Tenon
 - Flush mount 2-3/8" OD pole
 - Secure with 6 sets of concealed stainless steel screws
- **Ratings:** ETL, IP66 rated, suitable for wet locations
- **Warranty:** 5 years

Ordering Information

Product code	Voltage	Distribution	Wattage	CCT (K)	Finish	Optional
PT-EDS3	- U	- S	-	-	-	- *
	U- Uni. (100 - 277Vac)	S- Symmetrical	24W- 24W 35W- 35W 58W- 58W	30- 3000K 40- 4000K 50- 5000K	DB- Dark Bronze LG- Light Gray	

* Optional: N- No option; D- Dimmable; T- Dimmable with 3 timer modes; P- Photoelectric control

Note: Fixtures must be grounded in accordance with national, state, and/or local electrical codes. Failure to do so may result in serious personal injury

Mechanical Dimensions

