

Commercial Low Voltage (24Vdc) Recessed Downlight LED Luminaire

Project:

Location:

Catalog #:

Quantity:



Features

Teslyte TL-RLxx downlight series is specially design to be used with a 24VDC low voltage system, non-IC new construction commercial application. Available with interchangeable trims and reflectors for different beam angles. The TL-RL24 recessed luminaire will be a right product for commercial, hospitality, residential, or medical office applications, and the 24VDC version can be a perfect match for any facility with solar power systems.

- Frame construction:
 - Made of 16 gauge and powder coated cold roll steel
- LEDs:
 - Integral highly efficient LED module with CRI-80 or higher.
 - 24VDC input.
- Reflector and Lens
 - Combination of Reflector and Optical lens with 3 different beam spreads to provide 45, 60, 70-degree cut-off, wall-wash or diffused lens for general light distribution.
- Warranty:
 - UL listed, suitable for damp location.
 - 5 years warranty

Ordering Information

Product code	Distribution	CRI	Wattage	CCT (K)	Trim Finish	Optional
TL-RL24	-	-	-	-	-	N
TL-RL24 Voltage: 24V _{dc}	45 - 45° cut-off 60 - 60° cut-off 70 - 70° cut-off WA - Wall-Wash D - Diffused	8 - 80 9 - 90	10 - 10W (1500 lms) 15 - 15W (2000 lms)	27 - 2700K 30 - 3000K 35 - 3500K 40 - 4000K 50 - 5000K	W - White B - Black	N - No Option

Note: Fixtures must be grounded in accordance with national, state, and/or local electrical codes. Failure to do so may result in serious personal injury

Mechanical Dimensions

