

## **Energy Saving Retrofit Solutions**

**SOLUTIONS OVERVIEW:** Retrofit solutions can qualify for utility rebates, custom solutions available



## **BENEFITS**

- > Less expensive installation and maintenance costs
- > No disposal and recycling fees of the fixtures
- > More efficient
- > Qualifies for many utility rebate programs
- > Lighting can be upgraded to smart technology



## **FEATURED PROJECTS**

- > CAL State Northridge University Northridge, CA.
- > Laguna Niguel City Hall Laguna Niguel, CA.
- > Phoenix Sky Harbor International Airport Phoenix, AZ.
- > Laguna Hills Community Center Laguna Hills, CA.
- > Gilroy Gardens Family Theme Park City of Gilroy, CA.
- > Barney Schwartz Park Paso Robles, CA.



DLC Qualified Product List (QPL) & PG&E QPL listed





## **Retrofit Selection Guide**

Retroilt Selection Guide				
APPLICATION	SERIES	FEATURES	CERT.	TESLYTE ADVANTAGE
Area & Site	RF-TL	Wattages: 40W to 150W  Voltage: 120V-277V or 480V  Distribution: T3 CRI > 80  CCT: 3000K, 4000K, 5000K	C UL US	> All 40W to 150W part numbers are listed on DLC premium and PG&E QPL for rebates  > Multiple dimming levels, scheduling, monitoring with wireless NLC available
	RF-SZ	Wattages: 27W, 36W, 45W, 54W  Voltage: 120V-277V  Distribution: Symmetrical  CCT: 3000K, 4000K, 5000K		<ul> <li>&gt; Hard-wire to be eligible for rebates</li> <li>&gt; Extremely easy to install</li> <li>&gt; All 27W to 54W part numbers are listed on DLC QPL</li> </ul>
Post Top	RF-TD	Wattages: 40W, 50W, 60W, 80W  Voltage: 120V-277V or 480V  Distribution: T3, T5 CRI > 80  CCT: 3000K, 4000K, 5000K	MADE IN	<ul> <li>Real-time performance monitoring</li> <li>with Smart LED chip available</li> <li>High reliable flip chip LED technology</li> <li>available</li> </ul>
Wall/Ceiling Mount Step Light	RF-SL	Wattages: 6.5W, 13W  Voltage: 120V-277V  Distribution: Symmetrical	MADE IN	> On-site consultation for custom-fit available

CCT: 3000K, 4000K, 5000K