

Decorative Bollard ET5023



Project:

Location:

Catalog #:

Quantity:

Features

Teslyte ET5023 bollard featuring a sleek appearance of extruded aluminum column with choices of height and surface finish and creating an axially symmetric, broad, and uniform beam spread, ideally suited for illumination of pathways, entrances and access roads.

- Housing:
 - Extruded aluminum housing body
 - Die-cast aluminum housing top
 - Silicone rubber ring
- Light aperture
 - 360° Light distribution
- Optical Lens:
 - Polycarbonate lens
- Finish:
 - AkzoNobel powder coat with marine ambient corrosion resistance option
- Application:
 - Pathways, entrances, and access roads
- Warranty:
 - IP65
 - 3 years warranty

Ordering Information

Product code	Wattage	Height	Diameter	CCT(K)	Ra	Finish	Options
ET5023	- C10	- <input type="text"/>	- 6	- <input type="text"/>	- <input type="text"/>	- <input type="text"/>	- <input type="text"/>
Input Voltage: 120-277Vac	C10 - 10W	24 - 24" 32 - 32"	6 - 5.5"	30 - 3000K 40 - 4000K 50 - 5000K	80 - R80 90 - R90	B - Black W - White G - Gray Z - Mineral Bronze S - Silver	M - Marine ambient corrosion resistance DMG - 0-10V Dimming

Note: Fixtures must be grounded in accordance with national, state, and/or local electrical codes. Failure to do so may result in serious personal injury

Mechanical Dimensions & Photometric

