

## Decorative Bollard ET5024



Project:

Location:

Catalog #:

Quantity:

### Features

Teslyte ET5024 bollard featuring a sleek appearance of extruded aluminum column with choices of height and surface finish and creating an axially symmetric, broad, and uniform beam spread, ideally suited for illumination of pathways, entrances and access roads.

- Housing:
  - Extruded aluminum housing body
  - Die-cast aluminum housing top
  - Silicone rubber ring
- Light aperture
  - 360° Light distribution
- Optical Lens:
  - Polycarbonate lens
- Finish:
  - AkzoNobel powder coat with marine ambient corrosion resistance option
- Application:
  - Pathways, entrances, and access roads
- Warranty:
  - IP65
  - 3 years warranty

### Ordering Information

Product code	Wattage	Height	Diameter	CCT(K)	Ra	Finish	Options
<b>ET5024</b>	- <input type="text"/>	- <input type="text"/>	- <b>8</b>	- <input type="text"/>	- <input type="text"/>	- <input type="text"/>	- <input type="text"/>
Input Voltage: 120-277Vac	<b>C20</b> - 20W (not available for 42" height)  <b>C32</b> - 20W	<b>36</b> - 36" <b>42</b> - 42"	<b>8</b> - 7 7/8"	<b>30</b> - 3000K <b>40</b> - 4000K <b>50</b> - 4000K	<b>80</b> - R80 <b>90</b> - R90	<b>B</b> - Black <b>W</b> - White <b>G</b> - Gray <b>Z</b> - Mineral Bronze <b>S</b> - Silver	<b>M</b> - Marine ambient corrosion resistance  <b>DMG</b> - 0-10V Dimming

Note: Fixtures must be grounded in accordance with national, state, and/or local electrical codes. Failure to do so may result in serious personal injury

Mechanical Dimensions & Photometric

