

**LED Area and Site Luminaire**

Project:

Location:

Catalog #:

Quantity:



**BUY AMERICAN ACT  
COMPLIANT**


**Features**

Teslyte SB-TY Series is designed with the flexibility for customers requesting Buy American Act Compliant while adding greater style and scalability. This SB-TY series has ability of meet a wider range of area lighting needs and is a scalable lighting solution targeted for 8 feet to 20 feet mounting heights.

- Housing:
  - Die-cast aluminum for superior durability with heat sink and driver compartment
  - Silicone gaskets enable an IP65 rated
  - Stainless steel hardware with properly secure all components within the housing
- Lens : Clear Glass Lens, LED module integrated optics
- LEDs: Highly efficient LEDs and quality driver to ensure long lifetime
- Applications: pathway, parking lot, business complexes, residential neighborhoods and marina usage
- Mounting: Arm mount or slip-fitter
- Ratings: UL, IP66 rated, suitable for wet locations
  - Warranty: 5 years

**Ordering Information**

Product code	Voltage	Distribution	Wattage	CCT (K)	Finish	Optional
<b>SB-TY20</b>	- <input type="text"/>	- <input type="text"/>	- <input type="text"/>	- <input type="text"/>	- <input type="text"/>	- <input type="text"/>
	<b>U</b> - Univ. (100 -277Vac) <b>4</b> - 277 – 480V	<b>3</b> - Type III <b>5</b> - Type V	<b>100</b> - 100W <b>150</b> - 150W <b>180</b> - 180W	<b>30</b> - 3000K <b>40</b> - 4000K <b>50</b> - 5000K	<b>BR</b> - Bronze	<b>XX</b> - Mounting <b>Y</b> - Dimmable

\* Optional: **SP**- Direct mount to square pole; **RP**- Direct mount to round pole; **MA**- Horizontal mount arms  
**D**- Dimmable; **T**- Dimmable with 3 timer modes; **P**- Photoelectric control

Note: Fixtures must be grounded in accordance with national, state, and/or local electrical codes. Failure to do so may result in serious personal injury

**Mechanical Dimensions**
